

**SPECIFICATION**

INFO@INTERIOR-UMEÅ.SE

Product definition		: SAMBA
Gauge		: Cut-Pile
No. of tufts	ISO 1763	: 3/16
Pile fibre		: ± 52.500/m <sup>2</sup>
Pile weight		: 100% polyamide
Pile height	ISO 1766	: 1100 gr/m <sup>2</sup> ± 5%
Primary backing		: 6.8 mm ± 5%
Tile backing		: PA/PES non-woven – Colback
Total thickness	ISO 1765	: Polyflex with glass fibre scrim
Total weight		: 10.3 mm ± 5%
Tile size		: 4800 gr/m <sup>2</sup> ± 7,5% (± 137 oz/yd <sup>2</sup> )
Tiles per box		: 50 x 50 cm (± 19.7" x 19.7")
		: 16

**PERFORMANCE**

Use classification		: 33
Castor chair test	EN 985	: pass
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Thermal isolation	ISO 8302	: 0.19 m <sup>2</sup> K/W
Dimensional stability	EN 986	: pass

**ELECTROSTATIC PROPERTIES**

Walk on test	ISO 6356	: -0.4 kV
Stactic loading		: anti-static

**FLAME PROPERTIES**

Reaction to fire	EN ISO 11925-2	
	EN ISO 9239-1	: B <sub>fl</sub> – s1

**COLOUR FASTNESS PROPERTIES**

Light	ISO 105 B02	: 6.0
Rubbing, dry	ISO 105 X12	: 5.0
Rubbing, wet	ISO 105 X12	: 5.0
Water	ISO 105 E01	: 5.0
Water stains	EN 1307/G	: 5.0



**GENERAL**

Recommended maintenance:  
 Pile direction:

Best results are obtained when cleaned with a dry shampoo method.  
 Directional arrows are printed on the back of each tile.  
 Best results are obtained when laid checkerboard.

Laying instructions:

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m<sup>2</sup> it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

**COLOURS:**

<b>1795 Black</b>
<b>1885 Chocolate</b>
<b>1700 Silver</b>

<b>1350 Green</b>	<b>1670 Purple</b>
<b>1515 Orange</b>	<b>1110 Ivory</b>
<b>1950 Lavender</b>	<b>1920 Blue</b>